



www.unitedwindowmfg.com  
24-36 Fadem Road, Springfield NJ 07061

## 3800 - 3900 Single Hung Window

### Product Performance:

AAMA 101 Results:

Window Size	Configuration	AAMA Rating (psf)	Air (cfm/ft <sup>2</sup> )	Water (psf)
40" x 60"	Single-Sheetrock Pass thru	Class LC-PG35-H	0.15	5.43
72" x 72"	Twin-Sheetrock Pass thru	Class LC-PG35-H	0.20	5.43
44" x 75"	Single	Class LC-PG30-H	0.22	4.6
40" x 84"	Single	Class LC-PG40-H	0.26	6.06
36" x 74"	Single	Class LC-PG50-H	"	7.52
72" x 62"	Twin	Class LC-PG50-H	"	"
72" x 74"	Twin	Class LC-PG50-H	0.3	7.52
108" x 74"	Triple	Class LC-PG50-H	0.27	7.52
60" x 60"	Fixed	Class CW-PG50-FW	0.01	7.52
44" x 74"	Fixed	Class CW-PG50-FW	0.01	7.52
105" x 84"	Twin Fixed-Structural Mull	Class LC-PG50-FW	0.07	12.12

**Performance Grade** is a numeric designator that defines the performance of a product upon the completion of three tests, structural performance under wind load, resistance to water penetration and resistance to air leakage. The Performance Grade of a window unit is limited by the lowest performance rating of the three tests. The results apply to all window units smaller or equal to the window unit tested.

### Product Dimensions:

Vinyl Wall Thickness: 0.065"  
Typ. Glass Thickness: 3/4"  
Jamb Depth: 3.25"  
Mullion Adder: 1/2"  
Nail Fin Setback: 1.125"

### Rough Opening:

Window Width + 1/2"  
Window Height + 1/2"

### Size Restrictions:

	Min:	Max:
Width	18"	48"
Height	25"	84"

(Max. United Inches 144")

