

Expertly Crafted Windows & Doors

Since 1988 | Made in America



- High Quality Windows & Doors
- Orders Delivered On Time & Complete
- Industry-leading Service





SCAN &
LEARN

QUICK-LINKS™

Scan the QR code for more product information.



3800 Series
New Construction
Flat Frame
Single Hung



3900 Series
New Construction
Brickmould Frame
Single Hung



5800 Series
New Construction
Flat Frame
Double Hung



5900 Series
New Construction
Brickmould Frame
Double Hung



6000 Series
New Construction/
Replacement
Casement



7400 Series
Replacement
Double Hung



9600 Series
New Construction/
Replacement
Double Hung



4500 Series
Heavy Duty
Sliding Patio Door
New Construction



4700 Series
Knock Down (KD)
Sliding Patio Door
New Construction/
Replacement




CONTENTS

Black Quick-ship Program	1
3900/38, 5900/58 New Construction Windows	2
3" Exterior Casing	3
6000 Casement & 7400 Replacement Window	4
9600 Replacement/ New Construction Window	5
4500 & 4700 Sliding Doors	6
Shape Windows.....	7
Window Options.....	8
Door Options	9
Color Options.....	9
Patio Door Handing	10
Garden Window.....	10
Bay & Bow Windows	11
Energy Efficient Glass.....	12
Understanding the NFRC Label	13



Curb Appeal with Optional Window Casing



Shape Windows


PRODUCT DOCUMENTS



Scan the QR code for technical information
& helpful documents for homeowners,
builders & architects.

unitedwindowmfg.com/documents

The information presented in this catalog was checked for accuracy at the time it was published. United Window & Door is not responsible for errors or typos. United Window & Door reserves the right to update or change information pertaining to its products, services and warranties at any time. Confirm information is up to date and correct with customer service prior to placing an order.



BLACK QUICK-SHIP PROGRAM

Black windows & doors ship as fast as white windows & doors.



BE BOLD.

Black Windows & Doors Perfected

Introducing Onyx™ a revolutionary black acrylic coextrusion process in which our black colored acrylic material is molecularly bonded together with our white vinyl material as it is being formed, resulting in the most permanent bond in vinyl windows & doors to date.

BOLD COLLECTION

Black Onyx™
Acrylic Coextrusion
Exterior & Interior

Available in: 3900 6000
 4500 9600

Shown: Onyx™ Exterior with Onyx™ Interior



SEMI-BOLD COLLECTION

Any Combination of Black Onyx™
Acrylic Coextrusion with White.

Available in: 3800 5900
 3900 6000
 4500 7400

Shown: Onyx™ Exterior with Onyx™ Interior Sash
over a White Vinyl Interior Frame



3900

Single Hung

See Page 8-9 for
Options & Colors



Exterior



Interior

FEATURES

- 3 1/4" Frame Depth
- 3/4" Warm-Edge Insulated Glass
- Concealed Block & Tackle Balances
- Integrated Nail Fin with J-channel
- 3/0 X 5/0 Meets Egress



Tilts In
for Easy
Cleaning




Limited
Lifetime
Warranty



Energy
Efficient
Product




Half
Fiberglass
Mesh Screen



Brickmould Frame

3900



Flat Frame

3800



3900 Black Ext. / Black Int. with Farmhouse Grid

5900

Double Hung

See Page 8-9 for
Options & Colors



Exterior



Interior

FEATURES

- 3 13/16" Frame Depth
- 3/4" Warm-Edge Insulated Glass
- Concealed Block & Tackle Balances
- Integrated Nail Fin with J-channel
- Water-Repelling Sloped Sill



Tilts In
for Easy
Cleaning




Limited
Lifetime
Warranty



Energy
Efficient
Product




Full
Fiberglass
Mesh Screen



Brickmould Frame

5900



Flat Frame

5800



5900 Black Ext. / White Int. with Farmhouse Grid & Full Screen



Shown with 3" Exterior Casing - (1) Picture Frame

INSTANT CURB APPEAL

Easily add character without adding to installation time, with pre-applied three inch casing.



Shown without 3" Exterior Casing


FEATURES

- Available in White, Beige or Onyx™ Black Coextrusion*
- Factory Applied for Easy Install

Add Casing to the Following New Construction Window Types


- Single Hung
- Double Hung
- Casement
- Picture
- Select Shapes
- Slider

Available in 4 Styles




1

Picture Frame



2

Picture Frame with Decorative Back Banding



3

Picture Frame with Bull-Nosed Sill



4

Picture Frame with Decorative Back Banding and Bull-Nosed Sill

*(1) Picture Frame is available in any color.

6000

Casement

See Page 8-9 for
Options & Colors



Exterior



Interior

FEATURES

- 3 1/4" Frame Depth
- 3/4" Warm-Edge Insulated Glass
- Spring Loaded Fiberglass Mesh Screen for Easy Removal



Optional

Pegasus Hardware

Consolidates the window operator, lock & limiter into one mechanism.



Limited
Lifetime
Warranty



Energy
Efficient
Product



Full
Fiberglass
Mesh Screen



6000 Black Ext. / Black Int.

7400

Double Hung

See Page 8-9 for
Options & Colors



Exterior



Interior

FEATURES

- 3 1/4" Frame Depth
- 3/4" Warm-Edge Insulated Glass
- Constant Force Balances
- Water-Repelling Sloped Sill



Tilts In
for Easy
Cleaning




Limited
Lifetime
Warranty



Energy
Efficient
Product



Half
Fiberglass
Mesh Screen



7400 Black Ext. / White Int. with Colonial Grids

REPLACEMENT / NEW CONSTRUCTION

REPLACEMENT

9600

See Page 8-9 for
Options & Colors

Double Hung



Exterior



Interior

NEW



9600 Black Ext. / Black Int. with Farmhouse Grid

FEATURES

- 3 1/4" Frame Depth
- 3/4" Warm-Edge Insulated Glass
- Replicates the Look of a Wood Window
- Integrated Cellular Insulation
- 5/8" Integrated J-channel (fits most siding types)



Tilts In
for Easy
Cleaning



Limited
Lifetime
Warranty



Energy
Efficient
Product



Full
Fiberglass
Mesh Screen

REPLACEMENT / NEW CONSTRUCTION

Hardware Options



White



Brushed
Nickel



Black

Optional Features




Tilt &
Lock



Window Opening
Control Device (WOCD)

Thermal Efficiency



Integrated Cellular Insulation

Air Performance



Dual Seal + Interlock





Blinds Between
the Glass






Add-on
Nail Fin

4500**SLIDING PATIO DOOR**See Page 9 for
Options & Colors**FEATURES**

- 5 1/16" Frame Depth
- Multi-chambered Frame Design Adds Strength & Thermal Efficiency
- Reinforced Sash Panels
- Fusion Welded Heavy-duty Vinyl
- Stainless Steel Ball Bearings
- Integrated Nail Fin
- Available as 2 or 3 Panel Doors

**2-Panel****3-Panel**1-Point
Mortise
LockLimited
Lifetime
WarrantyEnergy
Efficient
ProductFiberglass
Mesh
Screen**4700****KNOCK DOWN (KD)
SLIDING PATIO DOOR**See Page 9 for
Options & Colors**FEATURES**

- 5 7/8" Frame Depth
- Ready to Assemble ("Knock Down")
- Each Component Weighs Less Than 80 lbs
- Easy Glide Steel Track with Stainless Steel Ball Bearings
- Patent Pending, Guide Pin Assembly System
- Pre-Applied Gasket; Door Stays Watertight
- Add-on Nail Fin
- Available as 2, 3 or 4 Panel Doors


**2-Panel****3-Panel****4-Panel**2-Point
Mortise
LockLimited
Lifetime
WarrantyEnergy
Efficient
ProductFiberglass
Mesh
Screen



PAR
Parallelogram



EB
Eyebrow



CIR
Circle




TRI
Triangle
Isosceles



EBX
Extended Eyebrow



ELX
Extended Ellipse



HEX
Hexagon



HEB
Half Eyebrow



CT
Circle Top




TRE
Triangle
Equilateral



CTX
Extended Circle Top



QRX
Extended Quarter
Round



PENT
Pentagon



HEBX
Extended Half
Eyebrow




QR
Quarter Round



TRR
Right Triangle



CATH
Cathedral



CATHX
Extended Cathedral



PTE
Pentagon
Equilateral



OCT
Octagon



OV
Oval



DIA
Diamond



EL
Ellipse



TRAP
Trapezoid

Shape Limitations

- Minimum radius on any shape is 11 3/4"
- Maximum width on a HR, HRX or Elliptical is 80"
- Maximum width for an EBX or EB is 105", unless the radius is 40" or less, then it is 80"
- Minimum height on an FB or Elliptical is width/3
- Maximum sq/ft on any unit is 45 sq/ft, larger units will need to be split into separate units
- Right/Left Triangle 19 1/2", wide minimum with a minimum leg height of (width/1.38)
- Isosceles Triangle 35 1/2", wide minimum with a minimum height of (width/1.6)
- Minimum minor radius on an oval or elliptical is 11"
- HEB or HEBX 18", wide minimum with a minimum radius of 11"
- Pentagons 19 1/2", wide minimum with a cut angle no less than 20°
- QR and QRX 19 1/2", wide minimum with a minimum radius of 11"
- Trapezoids 20", wide minimum with a cut angle no less than 20°
- Cathedrals 19 1/2", wide minimum with a minimum radius of 11"
- Shape legs must be a minimum of 6" TTT










CTX (Extended Circle Top) with SDL Gothic Grids



WINDOW OPTIONS

NOTE: These lists of features are not comprehensive. Contact customer service for any additional questions about product features.

		3800	3900	5800	5900	6000	7400	9600
Standard Features	3/4" Insulated Glass	●	●	●	●	●	●	●
	Integrated Nail Fin / J-channel	●	●	●	●	●		
	Block & Tackle Balances	●	●	●	●			
	Concealed Stainless Steel Constant Force Balances						●	●
	DP-50/PG-50 - 36x60"*	●	●	●	●	●	●	
	Brickmould Exterior Frame		●		●	†		
	Flat Exterior Frame	●		●				
	Beveled Exterior Frame						●	●
Optional Features	LowE & Argon	●	●	●	●	●	●	●
	WOCD, Vent Latches & Sash Limiters	●	●	●	●	●	●	●
	Structural Mullions	●	●	●	●	●	●	●
	Primed Extension Jamb	●	●	●	●	●		
	Drywall Pass-through	●	●					
	Blinds Between the Glass 1" IG					●		●
	Add-on Nail Fin							●
Available Window Types	 Twin	●	●	●	●	●	●	●
	 Triple	●	●	●	●	●	●	●
	 Picture	●	●	●	●	●	●	●
	 Slider	●	●	●	●		●	●
	 Shapes	●	●	●	●	●		
	 Awning					●		
	 Hopper						●	

*Any product greater than 36x60" will be subject to a different rating. Larger sizes may need additional reinforcement to meet DP-50/PG-50

†Modified Brickmould Frame

Grid Patterns



No Grid



Farmhouse



Colonial



French




Prairie




Diamond


Grid Types



Flat



Dimensional



SDL

Widths:

Flat 5/8" or 13/16"
Dimensional 3/4"
SDL 7/8" (Standard)
or 2" (Available)

Our Vinyl



Brilliance™

Brilliance™ vinyl products by United are not painted but are formed from a pure cloud white vinyl that's shined to a radiant semi-gloss finish.



United Window & Door utilizes a black acrylic coextrusion process in which our black colored acrylic material is molecularly bonded together with our white vinyl material as it is being formed, resulting in the most permanent bond in vinyl windows to date.

DOOR OPTIONS



Standard Features	4500	4700
Left or Right Handed	●	●
Stainless Steel Ball Bearings	●	●
DP-50/PG-50 - 72x80"*	●	
LowE & Argon	●	●
1" Insulated Glass	●	●

Optional Features

Primed Extension Jamb	●	
Blinds Between the Glass	●	●
Keyed Entry Handle-set	●	●

Handles

More Options Available



White



Satin Nickel



Black

Blinds Between the Glass



White



Satin Gray*


*Not Available in 4700



Beige*

*Not Available in 4700

Grid Types



Flat
5/8" or
13/16"



Dimensional
3/4"

Grid Patterns



No Grid



Colonial



French



Prairie

COLOR OPTIONS



Color Combinations Exterior / Interior


			3800	3900	5800	5900	6000	7400	9600	4500	4700
Solid Vinyl		Brilliance™ White / White	●	●	●	●	●	●	●	●	●
		Solid Beige Beige / Beige	●	●	●	●	●	●		●	
Acrylic Coextrusion		Onyx™ / Brilliance™ Black / White	●	●	●	●	●	●		●	
		Onyx™ Black / Black		●			●		●	●	
		Bronze / White Brilliance™		●		●	●	●		●	
Paint		Gray / White Brilliance™	●	●	●	●	●	●		●	
		Clay / White Brilliance™	●	●	●	●	●	●		●	
		Sable / White Brilliance™	●	●	●	●	●	●		●	
		Anthracite Grey / White Brilliance™	●	●	●	●	●	●		●	
		Green / White Brilliance™	●	●	●	●	●	●		●	
		Brick Red / White Brilliance™	●	●	●	●	●	●		●	
		Bronze / White Brilliance™	●	●	●	●	●	●		●	
		United Beige / White Brilliance™	●	●	●	●	●	●		●	

*Any product greater than 72x80" will be subject to a different rating. Larger sizes may need additional reinforcement to meet DP-50/PG-50




PATIO DOOR HANDING

2 Panel



Left Operating


Operating / Stationary
XO



Right Operating


Stationary / Operating
OX

3 Panel



Left Operating


Left Stationary / Operating / Right Stationary
OXO-L



Right Operating

Left Stationary / Operating / Right Stationary
OXO-R

4 Panel



Center Operating

Left Stationary / Primary Operating / Operating / Right Stationary
OXXO

Look at the door from the outside.

For the purpose of ordering, all United patio doors must now be described as OSLI (industry standard) which means from the "Outside Looking In".

When choosing the handing of your patio door (which panel operates and which is stationary) you must describe this as it appears from outside the home.



GARDEN WINDOW

REPLACEMENT



FEATURES

- Slim Line Frame
- Multi-point Locking System
- Optional Built-In Shelf
- Dual Weather Stripping
- Sloped Top Lite with Tempered Glass
- Operational or Stationary Side Casements



Limited Lifetime
Warranty
(Window Units)



Energy
Efficient
Product

BAY WINDOWS



FEATURES

- Bay window units come fully assembled from the factory
- Bay windows can be mulled into three-lite configurations at 30° or 45°
- Available in Double Hung, Casement or Picture Combinations




Limited Lifetime
Warranty
(Window Units)




Energy
Efficient
Product

30°



45°



REPLACEMENT

BOW WINDOWS



FEATURES

- Create a Dynamic View from the Inside with a Multi-lite Bow Window
- Bow Windows can be Mulled with 3 or More Lites at 10°
- Available in Double Hung, Casement or Picture Combinations



Limited Lifetime
Warranty
(Window Units)



Energy
Efficient
Product

3 Lite



4 Lite



5 Lite



6 Lite




REPLACEMENT




ENERGY EFFICIENT GLASS



ENERGY STAR® for Windows, Doors, and Skylights
CLIMATE ZONE MAP



Low-E, or low emissivity energy-efficient windows, have a thin transparent coating that reflects heat and UV light keeping the temperature in your home comfortable. Our double pane windows contain Low-E coatings in various configurations; optimized for your designated climate zone. Optional, heavier-than-air **argon gas** must also be included to meet energy requirements.



UNDERSTANDING THE NFRC LABEL




U-Factor (UF)

A rating based on how much heat is allowed to transfer through the product. The lower the U-factor, the less heat transfer occurs through a product. U-factor is particularly important during the winter heating season in colder climates.



Solar Heat Gain Coefficient (SHGC)

A rating based on how much heat from the sun is blocked. The lower the SHGC, the more a product is blocking solar heat gain. Blocking solar heat gain is particularly important during the summer cooling season in hot Southern climates. By contrast, people in Northern climates may want solar heat gain during the cold winter months to lessen the cost of heating the home.



Visible Light Transmission (VLT)

A rating based on how much visible light comes through a product. The higher the VLT, the higher the potential for day lighting.



Air Leakage

A rating based on how much air will enter a room through the product. Lower number, the lower the potential for a draft.



QUALITY

SERVICE



Four generations of innovation and expertise go into every window and door manufactured by United. Matched with some of the best warranties in the industry, you can be sure you are getting a quality product that lasts.

INNOVATION



© 2024 United Window & Door

24 Fadem Road
Springfield, NJ 07081
Office (800) 848-4550
Fax (973) 912-8866
unitedwindowmfg.com
032124v2